

TDS HEMLOCK XL-550

LET US
HELP YOU
ACHEIVE
YOUR GOALS

Hemlock
THE ART OF FLOORING *XL-550*

Click Vinyl Tile is an innovative form of vinyl flooring. It is becoming an increasingly popular and affordable alternative to wood or stone. The realistic look of either wood, stone or cerraimitile isxtremely hard wearing and resilient to daily wear and tear. it has a scratch resistant surface and waterproof making it ideal for any area.

The product is made up of multiple thin layers so that the flooring is s still flexible but very durable and easy to look after Click system ensures fast & simple installation

CHARACTERISTICS STANDARD RESULT

Size	EN 427	226mm x 1525mm
Squareness / Straightness	EN 427	>0.2mm
Overall Thickness	EN 428	5.0mm
Wear Layer Thickness	EN 428	0.5mm
Warp	EN 434	±0.5mm (80°C, 6h)
Peeling Resistance	EN 431	Length 106.8N, Width 108.9N
Dimensional Stability	EN 434	>0.1 %(80°C, 6h)
Wear Resistance	EN 660-2	≥0.015g/1000turns
Slip Resistance	DIN 51130	R9
Castor chair test	EN 425	No delamination
Residual Identation	EN 433	>0.1mm
Mildew Resistance	ASTM G21	Level 1
Toxicity	EN 71-3	Pass
Corrosion Resistance	EN 423	Level 0
Color Fastness	ISO 105 B02	<6
Fire Resintance	ASTM E84-03	Bfl-S1
Gloss	—	+2gu