



VALIANT

CLICK 550



VT 55014
180MM*1220MM



VT 55014
180MM*1220MM

The image displays a close-up, vertical view of a wood grain texture. The wood has a light tan or beige color with prominent, wavy, vertical grain patterns. The texture is smooth and consistent across the surface.

VT 55015
180MM*1220MM



VT 55015


180MM*1220MM

The image displays a detailed, close-up view of a wood grain texture. The color is a dark, muted grey, and the grain pattern is highly detailed, showing various wavy and linear patterns characteristic of wood. The texture is uniform across the entire surface.

VT 55018
180MM*1220MM



VT 55018
180MM*1220MM

The image shows a close-up of a light-colored wood surface with a prominent vertical grain. The wood has a warm, golden-brown hue and features several large, vertically oriented knots and wavy grain patterns. The texture is smooth and natural.

VT 55020
180MM*1220MM



VT 55020
180MM*1220MM

The image shows a close-up, vertical view of a wood grain. The wood has a warm, medium-brown tone with a prominent, wavy grain pattern. There are several knots and natural imperfections visible throughout the surface, giving it a rustic and organic appearance. The lighting is even, highlighting the texture of the wood fibers.

VT 55017
180MM*1220MM



VT 55017
180MM*1220MM

The image shows a close-up of a dark brown wood surface with a vertical grain pattern and several knots. The lighting is slightly uneven, creating subtle gradients of brown.

VT 55019

180MM*1220MM



VT 55019
180MM*1220MM



VT 55016
180MM*1220MM



VT 55016
180MM*1220MM

VT 55021
305MM*610MM



VT 55021
305MM*610MM



VT 55023
305MM*610MM



VT 55023
305MM*610MM

VT 55022
305MM*610MM



VT 55022
305MM*610MM

LET US
HELP YOU
ACHEIVE
YOUR GOALS



- ① UV coating
- ② High-density wear layer
- ③ Printing layer
- ④ Fiber-glass layer*
- ⑤ Backing layer

Click Vinyl Tile is an innovative form of vinyl flooring. It is becoming an increasingly popular and affordable alternative to wood or stone. The realistic look of either wood, stone or ceramic tile is extremely hard wearing and resilient to daily wear and tear. It has a scratch resistant surface and waterproof making it ideal for any area.

The product is made up of multiple thin layers so that the flooring is still flexible but very durable and easy to look after. Click system ensures fast and simple installation.

CHARACTERISTICS

STANDARD

RESULT

Size	EN 427	Wood 180mm*1220mm/Concrete 305mm*610mm
Squareness / Straightness	EN 427	<0.2mm
Overall thickness	EN 428	5.0mm
Wear Layer thickness	EN 428	0.5mm
Warp	EN 434	±0.5mm (80°C, 6h)
Peeling resistance	EN 431	Length 106.8N, Width 108.9N
Dimension stability	EN 434	<0.1% (80°C, 6h)
Wear resistance	EN 660-2	≤0.015g/1000turns
Slip resistance	DIN 51130	R9
Castor chair test	EN 425	No delamination
Residual indentation	EN 433	<0.1mm
Mildew resistance	ASTM G21	Level 1
Toxicity	EN 71-3	Pass
Corrosion resistance	EN 423	Level 0
Color fastness	ISO 105 B02	>6
Fire resistance	ASTM E84-03	Bfl-S1
Gloss	-	±2gu