

## TECHNICAL DATA

DESCRIPTION			
Total thickness	EN428	mm	2.0
Weight	EN430	g/m <sup>2</sup>	3400
Width	EN426	m	2
Length	EN427	m	20

CLASSIFICATION			
European classification	EN695	Class	34/43
Fire rating	EN13501-1	Class	Bs-s1
Static electrical propensity	EN1815	KV	<2
Slip resistance	DN51130	Class	R9

PERFORMANCE			
Wear resistance	EN660	mm <sup>3</sup>	≤3.5
Abrasion group	EN649	Group	P
Dimension stability	EN434	%	≤0.4
Flexibility	EN435	-	No crack
Residual indentation	EN435	mm	≤0.04
Color fastness	EN105-B02	Degree	≥6
Stain and chemical resistance	EN423	-	Good
Toxicity tests	B56853	-	<0.3
Castor chair test	EN425	-	OK
Thermal conductivity	EN12667	W/m.K	0.05
Impact sound reduction	EN17172	dB	Approx.4
Surface treatment	-	-	PUR+
Anti-bacterial activity	ISO22196	-	OK

ENVIRONMENT / INDOOR AIR QUALITY			
TVOC after 28 days	ISO16000	µg/m <sup>3</sup>	<10
Formaldehyde emission	EN14041	Class	E1
PCP	EN14041	-	ND

### INSTALLATION

Laying is the responsibility of the installer. Installation should be made in accordance with installation guidelines supplied and regularly updated by Cflors Technical Department. Installation should be carried out in accordance with local standards. Subfloor to be smooth, hard, clean and dry prior to laying. Where applicable, the subfloor must incorporate an effective Damp Proof Membrane. The material must be allowed to acclimatise 24 hours prior to installation in a room temperature of between 18-24°C.

### MAINTENANCE

Maintenance should be carried out regularly to retain the appearance and durability of the floor. The floor covering should be maintained with regular sweeping and damp mopping using a neutral cleaner, or auto scrubber machinery with an appropriate pad.

### ATTENTION

Rubber leaves indelible stains on vinyl floorings; do not use mats with rubber backing and replace tubular furniture feet with those made of PVC or polyamide. Place mats of sufficient length at entrances to reduce outside sources of dirt.

Further installation and maintenance instruction guides are available from Cflors.

## APPLICATIONS

HEALTH CARE  
HOSPITAL  
EDUCATION  
OFFICE  
RETAIL  
FACTORY

VICTORIA



# VICTORIA

COMMERCIAL HOMOGENEOUS VINYL FLOORING

DIRECTIONAL HOMOGENEOUS SHEET

**Cflors**  
The Flooring Solutions

### Head Office

Hudson Bay Center  
2 Bloor Street East, Suite 3500  
Toronto, Ontario, Canada | M4W 1Z8  
Tel: +1-416-915-4222  
Fax: +1-416-929-3174  
Email: info@cflors.com

### Regional Office

Cflors Middle East FZE  
LOB 7, Office 7F17 Jafza North  
Jebel Ali Free Zone, Dubai  
United Arab Emirates  
Tel: +971-4-898-9200  
Email: msa@cflors.com

**Cflors**  
The Flooring Solutions


VICTORIA SERIES HOMOGENEOUS VINYL FLOORING



1010




1001



1009



1059



1040



1060



1002



1035



1055



1032



1004



1033



1007



1037



1057



1000



1036



1056

2mm Thickness | PUR+ Treatment | 100% recyclable