

## Whitehorse

### **Specifications**

Construction:	multi-level loop
Fiber:	Universal Nylon 66
Dye Method:	Solution dyed
Gauge:	1/12"
Stitches:	10 per inch
Pile Weight:	20 OZ/yd <sup>2</sup> (680 gms/m <sup>2</sup> )
Pile Height:	4mm ± 0.5mm
Total Thickness:	10mm ± 0.5mm
Backing:	Mix- bac
Tile Size:	50cm x 50cm

### **Performance**

Flammability:	Passes (ASTM E648 / FF 1-70 (8/8))
Smoke Density:	Passes (ASTM E662)
Static Propensity:	≤ 3.0 kV (AATCC 134)
Soil & Stain Protection:	Excellent Soil Resistance
Colour Fastness to Light:	5 (AATCC- 16E)
Colour Fastness to Crocking:	5 (AATCC- 165)
Colour Fastness to Ozone:	5 (AATCC- 129)
Dimensional Stability:	<0.2% (AACHEN)
Dynamic Crush:	Negligible Impact or no change
Delamination Strength:	Excellent (No Separation)

### **Warranties**

10 years limited warranty.

No more than 10% face yarn loss by weight under normal use.

Limited static warranty.

Limited delamination warranty under normal use.























